



DRY, UNBEDDED STATIC TORQUE = 12 Nm

FOR APPLICATIONS INVOLVING DYNAMIC TORQUE  
PLEASE CONSULT OUR ENGINEERING DEPARTMENT

FOR 24 VOLT d.c. OPERATION

POWER CONSUMPTION AT 20°C = 16 WATTS

**BRAKE MASS = 0,87 kg**

$$\text{INERTIA} = 0,000029 \text{ kgm}^2$$

BACKLASH = 0.75° TYPICAL

RESPONSE TIME (WITHOUT DIODE) =

RESPONSE TIME (WITH DIODE) =

RELEASE TIME =

①

THIS DRAWING IS THE PROPERTY OF MATRIX INTERNATIONAL LIMITED AND IT MAY NOT BE COPIED OR USED FOR ANY PURPOSE EXCEPT DIRECTLY FOR THE COMPANY WITHOUT THEIR PRIOR WRITTEN CONSENT NOR IS IT TO BE SHOWN TO ANY THIRD PARTY.

THE FOLLOWING CONDITIONS APPLY UNLESS OTHERWISE STATED.

1. DIMENSIONS IN MILLIMETRES (mm).
2. SURFACE TEXTURE VALUES IN  $\mu\text{m Ra}$   $\frac{32}{\sqrt{}}$
3. UNTREATED/ MACHINED DIMENSIONS  $\pm 0.25\text{mm}$
4. SCALE 1:1.

1EB024-39

DRAWING NUMBER	ISSUE
----------------	-------

3	18891	19/03/07
2	18718	16/08/05
1	-	04/07/03