



BINDER CLUTCHES & BRAKES

## SPRING-APPLIED SINGLE-DISC BRAKE

76 43108H00

76 431 ..H00



VARIO LINE

POWER OF PARTNERSHIP AND MAGNETISM

## Kendrion Power Transmission

Our company's strength is measured by the delivery of products, performances, as well as a high degree of esteem towards our customers. KENDRION POWER TRANSMISSION is striving to develop a long-term relationship with its

customers and to cultivate this relationship under the motto "Power of Partnership". Ambitious aims can only be realised through a close and productive co-operation with our customers.

## BINDER CLUTCHES & BRAKES

The development of high-quality standard products as well as optimised tailor made solutions is the foundation of all our actions.

Power of Partnership stands for a co-operation with the Kendrion employees without bureau-cracy, ensuring a long and successful partnership with our customers.

## Top Market Knowledge...

the realisation of market orientated products are the results of our competence in electromagnetism which has been achieved with decades of experience and knowledge. The development of most innovative concepts and the

use of the most modern technologies in our research department together with the use of the latest production and logistic processes are our strengths.

Our customers profit from the individual solutions for high volume as well as the availability of individual products on the basis of a standard platform.

Our know-how is growing steadily hand in hand with the constant optimisation of every business process.

## Optimal tailor made solutions...

are not empty promises. The profound understanding of the Power of Magnetism at KENDRION POWER TRANSMISSION is the source of the research/development of market orientated products. Continuous expansion of the technological possibilities

enables us to be in the position to offer optimal solutions of brakes and clutches for numerous applications. We lay great emphasis on being able to offer solutions for different applications such as:

**... SECURING  
... STOPPING  
... POSITIONING  
... ACCELERATING.**

## Important synergies as a basis for success...

KENDRION POWER TRANSMISSION is a European company with a local presence in all economic regions of the world. Integrated in and yielding performance to the Kendrion Holding N.V., which is noted on the Amsterdam stock exchange, as a successful company with an annual turnover of 1,8 billion EUR; and approx. 5500 employees all over the world.

This is an excellent basis to realise, secure and enable our long-term goals and company objectives. A network of connected companies within Kendrion is another valuable factor for the success of KENDRION POWER TRANSMISSION. We live the "Power of Partnership" in a firm exchange

of expertise and business relationship within these companies.



Kendrion Power Transmission protects people and the environment





## Contents

### General technical information

**76 43108H00**

**76 431..H00**



**www.KendrionAT.com**

### Product line information

### BINDER CLUTCHES & BRAKES



The VARIO LINE is comprised of DC operated spring-applied single-disc brakes. Due to the great variety of brakes included in this line, the products can be ideally tailored to specific applications.

Electromagnetically operated spring-applied brakes generate the braking torque when voltage is removed. The braking effect can be neutralised by the electromagnetic force or by an additional hand release feature. The fitting dimensions and brake sizes within the VARIO LINE are specifically tailored to IEC motors.

### Versions

76 43108H00	torque range 1 - 4 Nm DC adjustable torque
76 431..H00	torque range 4 - 400 Nm DC adjustable torque

### Applications

- Machining equipment
- DC motors
- Material handling vehicles
- Gear motors
- Equipment manufacturing industry
- Handling technology
- Lifting and materials handling technology
- IEC three-phase motors
- Medical technology
- Paper-making and printing machines
- Wheelchairs
- Textile machines
- Gate drives
- ...

### Information on technical data included in the data sheets

The information provided in the operating instructions must be strictly adhered to when designing a machine (e.g. motor) and when using the brakes. The brakes are manufactured and tested in compliance with DIN VDE 0580 requirements. The insulation materials used conform with thermal class F norms. Operation of the brake as a pure holding brake without friction work is only permitted after prior consultation with the manufacturer. The specified times apply to the following conditions: separate switching of the brake, operating

temperature, rated voltage, and rated air gap. All values are mean values that are subject to variation. In the case of AC brake switching, the coupling time  $t_1$  is substantially longer.  $W_{max}$  (maximum switching energy) is the switching energy that must not be exceeded during braking operations at max. 1500 rpm. Braking operations at  $>1500$  rpm lead to a substantial reduction in the maximum admissible switching energy per switching operation. Such operations are only permitted after prior consultation with the manufacturer. The maximum switching power

$P_{max}$  is the switching energy  $W$  that can be converted by the brake per hour. In the case of applications where the number of switching operations per hour is greater than 1 ( $Z>1$ ), the diagram ( $W_{max}$  as a function of the number of switching operations per hour  $Z$ ) shown in the operating instructions applies. The  $P_{max}$  and  $W_{max}$  values are approximate values; they apply to applications where the brake is installed between the B-face end shield of the motor and the motor fan. The specified rated torques  $M_2$  characterise the torque level of the brakes. Depending on the

application of the brake, the switching torque  $M_1$  and the transmissible torque  $M_4$  may differ from the specified  $M_2$  values. The switching torque  $M_1$  depends on the speed (rpm). If the friction surfaces are contaminated with oil, grease or dirt the transferable torque  $M_4$  and the switching torque  $M_1$  may drop.

All technical data is subject to the running-in process of the brake being completed. Vertical operation of the brake is only permitted after prior consultation with the manufacturer.

## SPRING-APPLIED SINGLE-DISC BRAKE DC

<b>Version</b>	76 43108H00
<b>Standard rated voltages</b>	24V, 102V, 178V, 205V DC
<b>Protection</b>	IP 55 (if installed under motor fan hood) IP 65 (with accessories and if installed under motor fan hood)
<b>Thermal class</b>	F
<b>Rated torques</b>	1 - 4 Nm
<b>Accessories (options)</b>	friction plate, hand release feature, mounting screws, protective cover, screw plugs, sealing rings

Specification subject to change without notice.  
The "General technical information" and the "Operating instructions" 76 43108H00 must be strictly observed.




Photo: 76 43108H00

### Technical data


Size	Rated torque range (standard)	Max. reachable rated torque with fully screwed in adjustment ring	Max. speed	Max. switching power	Max. switching energy (Z=1)	Rated power	Response times		Moment of inertia hub and friction disc	Weight
							on	off		
08	M <sub>2</sub> [Nm]	M <sub>2</sub> max [Nm]	n <sub>max</sub> [rpm]	P <sub>max</sub> [kJ/h]	W <sub>max</sub> [kJ]	P <sub>N</sub> [W]	t <sub>1</sub> [ms]	t <sub>2</sub> [ms]	J [kgcm <sup>2</sup> ]	m [kg]
08	1 - 4	5	10 000	200	25	23.5	18	30	0.32	0.61

The service life values (W<sub>tot</sub>) specified in the table refer to the maximum rated torque (standard) and apply if the brake is adjusted twice.

### Ordering data (to be fully specified)

<b>SPRING-APPLIED SINGLE-DISC BRAKE</b>	
Please specify requested version	
<b>1</b>	Mounting pitch circle diameter <input type="checkbox"/> pitch circle diameter Ø 72 mm <input type="checkbox"/> pitch circle diameter Ø 75 mm
<b>2</b>	Corrosion protection <input type="checkbox"/> with corrosion protection <input type="checkbox"/> without corrosion protection
<b>3</b>	Coil voltage (standard 24 V, 102 V, 178 V, 205 V) Voltage: _____ V DC
<b>4</b>	Rated torque M <sub>2</sub> (standard) Size 08: 4 Nm Rated torque M <sub>2</sub> : _____ Nm

<b>HUB</b>	
<b>1</b>	Corrosion protection <input type="checkbox"/> with corrosion protection <input type="checkbox"/> without corrosion protection
<b>2</b>	Bore diameter (standard), groove JS9 as per DIN 6885, sheet 1 / sheet 3  Size 08: Ø 10, Ø 12, Ø 15 mm  Bore diameter: _____ mm  <input type="checkbox"/> or pilot bore



Size	d	$d_1$	$d_2$	$d_3$	$d_4$ (H7)	$d_5$	$d_6$	$d_7$	$d_8$	$d_9$	$d_{10}$	$d_{11}$	b	$b_1$	$b_2$	$b_3$
08	82	17	26	5	9 <sup>1)</sup> / 15 <sup>2)</sup>	72 / 75	85.5	42	64	4	16	3.8	33.5	13.7	12	7

Size	$b_4$	$b_5$	$b_6$	$b_7$	$b_8$	h	$h_1$	L	$L_1$	$L_2$	$L_3$	$L_4$	s	$s_{max}$ <sup>3)</sup>	M	$F^4)$ [N]	$\alpha$
08	36	14	1	3-6	91.5	51	90	18	1.8	400	6	30	0.2	0.5	3xM4	30	ca. 2°

<sup>1)</sup> Min. bore with keyway JS9 as per DIN 6885, sheet 1.<sup>2)</sup> Max. bore with keyway JS9 as per DIN 6885, sheet 1.Shaft ISO fitting K6. (1<sup>1), 2<sup>2)</sup>)</sup><sup>3)</sup> Max. air gap referred to max. rated torque (standard) up to brake adjustment or friction disc replacement.<sup>4)</sup> Release force F (approx.) referred to max. rated torque (standard).

## Accessories

Size	Friction plate	Hand release feature	Mounting screws				Protective cover <sup>5)</sup>		Sealing ring <sup>6)</sup>	Screw plugs
			Screw	Rated torque	Material number	Screws per brake	without hand release	with hand release		
08	76 43108A0004	76 43108A01940	DIN 7984-M4 x 25-8.8	3 Nm	304 510	3	76 43108A00005	76 43108A01005	326 000	412 817

<sup>5)</sup> Friction plate required<sup>6)</sup> 3 sealing rings for mounting screws

## SPRING-APPLIED SINGLE-DISC BRAKE DC

<b>Version</b>	76 431..H00
<b>Standard rated voltages</b>	24V, 102V, 178V, 205V DC
<b>Protection</b>	IP 55 (if installed under motor fan hood) IP 65 (with accessories and if installed under motor fan hood)
<b>Thermal class</b>	F
<b>Rated torques</b>	4-400 Nm
<b>Accessories (options)</b>	friction plate/flange, hand release feature, mounting screws, protective cover, screw plugs, sealing rings

Specification subject to change without notice.  
The "General technical information" and the "Operating instructions" 76 431..H00 must be strictly observed.




Photo: 76 43110H00

### Technical data


Size	Rated torque range (standard)	Max. reachable rated torque with fully screwed in adjusting ring M <sub>2</sub>	Max. speed n <sub>max</sub>	Max. switching power P <sub>max</sub>	Max. switching energy (Z=1) W <sub>max</sub>	Rated power P <sub>N</sub>	Response times		Moment of inertia hub and friction disc J	Weight m
							on	off		
10	4 - 8	10	3500	320	30	26	20	95	1.2	1.3
11	8 - 16	20	3500	430	41	30	30	80	2	2.8
13	16 - 32	40	3500	650	50	40	45	90	6	3.7
14	30 - 60	65	3500	800	55	53	85	85	8	5.7
16	40 - 80	100	3500	1000	58	55	90	190	16	8.4
19	80 - 150	170	3000	1200	65	80	130	270	38	13.1
24	150 - 240	300	3000	1400	80	110	225	235	108	22
29	280 - 400	600	3000	1600	275	130	115	560	230	36

The service life values (W<sub>tot</sub>) specified in the table refer to the maximum rated torque (standard).

### Ordering data (to be fully specified)

<b>SPRING-APPLIED SINGLE-DISC BRAKE</b>	
Please specify requested version	
<b>1</b>	Size (10, 11, 13, 14, 16, 19, 24, 29) Size: _____
<b>2</b>	Coil voltage (standard 24 V, 102 V, 178 V, 205 V) Voltage: _____ V DC
<b>3</b>	Optional hand release feature <input type="checkbox"/> with optional hand release <input type="checkbox"/> without optional hand release
<b>4</b>	Corrosion protection <input type="checkbox"/> Corrosion protection (enhanced) <input type="checkbox"/> Corrosion protection (standard)
<b>5</b>	Rated torque M <sub>2</sub> (standard) Size 10: 8 Nm    Size 29: 400 Nm Size 11: 16 Nm Size 13: 32 Nm Size 14: 60 Nm Size 16: 80 Nm Size 19: 150 Nm Size 24: 240 Nm Rated torque M <sub>2</sub> : _____ Nm

<b>HUB</b>	
<b>1</b>	Size (10, 11, 13, 14, 16 19, 24, 29) Size: _____
<b>2</b>	Corrosion protection <input type="checkbox"/> Corrosion protection (enhanced) <input type="checkbox"/> Corrosion protection (standard)
<b>3</b>	Bore diameter (standard), groove JS9 as per DIN 6885, sheet 1 Size 10: Ø 15, Ø 18, Ø 20 mm    Size 29: Ø 40, Ø 45, Ø 60 mm Size 11: Ø 15, Ø 20, Ø 22 mm Size 13: Ø 22, Ø 25, Ø 30 mm Size 14: Ø 20, Ø 25, Ø 30 mm Size 16: Ø 25, Ø 30, Ø 35 mm Size 19: Ø 30, Ø 40, Ø 45 mm Size 24: Ø 40, Ø 45, Ø 50 mm Bore diameter: _____ mm <input type="checkbox"/> or pilot bore



Size	d	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub> (H7)	d <sub>5</sub>	d <sub>6</sub> ca.	d <sub>7</sub>	d <sub>8</sub>	d <sub>9</sub>	d <sub>10</sub>	d <sub>11</sub>	d <sub>12</sub>	d <sub>13</sub>	b	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub> <sup>a)</sup>	b <sub>4</sub> <sup>a)</sup>	b <sub>5</sub>	b <sub>6</sub>	b <sub>7</sub>	h	h <sub>1</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	s	s <sub>max</sub> <sup>3)</sup>	s <sub>1</sub>	M	F <sup>5)</sup> [N]	α ca.	β
10	100	24	35	5	11 <sup>9</sup> /20 <sup>a</sup>	90	111	60	-	6	25	44	5.2	-	42	38.5	18	8	53	7	1.5	3.5-6.5	62	115	20	2.5	400	6	30	0.2	0.8	1	3xM5	25	10°	3x120°
11	127	30	40	4.2	13 <sup>9</sup> /23 <sup>a</sup>	112	136	68	-	8	25	58	5.2	-	52	47.5	25	8	61	8	1.5	4.0-8.0	78	125	20	3.5	400	6	30	0.2	0.95	1	3xM6	30	10°	3x120°
13	147	35	50	5.2	18 <sup>9</sup> /30 <sup>a</sup>	132	159	82	-	8	32	70	5.2	-	55.5	52	22	10	74	8	1.5	5.0-10.0	86	140	25	3	400	6	30	0.25	0.8	1.25	3xM6	60	10°	3x120°
14	164	35	50	5.2	18 <sup>9</sup> /30 <sup>a</sup>	145	179	82	-	10	40	61	5.2	-	61.5	55.5	28.5	10	74	8	1.5	5.0-10.0	96.5	152.5	30	3	400	6	30	0.3	0.9	1.5	3xM8	110	10°	3x120°
16	188	45.5	60	5	25 <sup>9</sup> /40 <sup>a</sup>	170	203	102	-	10	40	61	5.2	-	70	65	25	10	94	8	1.5	5.5-11.5	110	175	30	3	600	6	30	0.35	1.2	1.5	3xM8	130	10°	3x120°
19	215	51	75	6	30 <sup>9</sup> /45 <sup>a</sup>	196	230	116	100	10	40	77	5.2	9 6x60°	83	70.5	29	10	108	13	1•	6.0-14.5	134	210	35	4	600	6	30	0.35	1.5	1.7	6xM8	200	10°	6x60°
24	252	69.5	124	10.1	35 <sup>9</sup> /60 <sup>a</sup>	230	268	156	120	14	40	90	5.2	11 6x60°	97	89	36	-	-	17	1•	7.0-15	148	230	40	5	750	6	30	0.4	1.5	2	6xM10	270	10°	6x60°
29	302	89	124	10	40 <sup>9</sup> /70 <sup>a</sup>	278	321	156	278	14	40	120	5.2	11 6x60°	107	100	57.5	-	-	13.5	12.5	7.0-13.5	175	445	50	4.5	700	6	30	0.45	1.5	2.5	6xM10	200	10°	6x60°

<sup>1)</sup> Min. bore with feather key groove JS9 as per DIN 6885, sheet 1.

<sup>3)</sup> Max. air gap referred to max. rated torque (standard) up to friction disc replacement.

<sup>2)</sup> Max. bore with feather key groove JS9 as per DIN 6885, sheet 1.

<sup>4)</sup> Except for sizes 24 and 29.

Supporting feather key over entire length. Shaft ISO fitting k6. (1, 2)

<sup>5)</sup>) Release force F (approx.) referred to max. rated torque (standard).

## Accessories

Size	Friction plate/flange <sup>6)</sup>	Hand release feature	Mounting screws				Protective cover <sup>7)</sup>	Screw plugs	Sealing ring	
			Screw	Rated torque	Material number	Screws per brake			Order number	Rings per brake
10	76 43110H00004	76 43110H00940	ISO 4762 - M5 x 45	6 Nm	304 065	3	76 43110H00005	412 859	326 005	3
11	76 43111H00004	76 43111H00940	ISO 4762 - M6 x 55	10 Nm	304 051	3	76 43111H00005	412 842	326 006	3
13	76 43113H00004	76 43113H00940	ISO 4762 - M6x 60	10 Nm	304 052	3	76 43113H00005	412 843	326 006	3
14	76 43114H00004	76 43114H00940	ISO 4762 - M8x 70	25 Nm	304 078	3	71 10116A3013	412 843	326 007	3
16	76 43116H00004	76 43116H00940	ISO 4762 - M8 x 75	25 Nm	304 079	3	76 43116H00005	412 860	326 007	3
19	76 43119H00024	76 43119H00940	ISO 4762 - M8 x 80 <sup>8)</sup>	25 Nm	304 080	6	76 43119H00005	412 841	326 007	6
24	76 43124H00024	76 43124H00940	ISO 4762 - M10x 100 <sup>8)</sup>	40 Nm	304 117	6	76 43124H00005	412 885	326 008	6
29	76 43129H00024	76 43129H00940	ISO 4762 - M10x 110 <sup>8)</sup>	40 Nm	304 118	6	76 43129H00005	-	326 008	6

<sup>6)</sup>) Sizes 10 - 16: friction plate; sizes 19 - 29: flange.

<sup>8)</sup>) Screw length if no flange is used.

7) Friction plate or flange required.

Operation of hand release feature only possible in the direction opposite the mounting surface.



## Vertretungen/ Representatives

### Belgien, Luxemburg/ Belgium, Luxembourg

#### Bintz technics N. V.

Brixtonlaan 25, Business Park  
1930 Zaventem  
Belgien/ Belgium  
Tel. +32 (0) 7 20 49 16  
Fax +32 (0) 7 20 37 50

### Dänemark/ Denmark

#### Lind Jacobsen & Co. A/S

Blokken 62  
3460 Birkerrad  
Dänemark/ Denmark  
Tel. +(45) 45 81 82 22  
Fax +(45) 45 82 10 22  
strong@lind-jacobsen.dk  
www.lind-jacobsen.dk

### Deutschland/ Germany

Steinlen Elektromaschinenbau  
GmbH  
Ehlbeck 21  
30938 Burgwedel  
Deutschland/ Germany  
Postfach 12 25 (PLZ 30928)  
Tel. +49 (0) 51 39 80 70-0  
Fax +49 (0) 51 39 80 70-60  
www.steinlen.de

#### Klebs + Hartmann GmbH & Co. KG

August-Heller-Straße 3  
67065 Ludwigshafen  
Deutschland/ Germany  
Postfach 11 56 (PLZ 78080)  
Tel. +49 (0) 62 15 79 00-0  
Fax +49 (0) 62 15 79 00-95  
www.klebs-hartmann.de

#### ELMATEC

Straub und Müller GmbH  
Benzstraße 2  
78083 Dauchingen  
Deutschland/ Germany  
Postfach 11 56 (PLZ 78080)  
Tel. +49 (0) 77 20 95 71 71  
Fax +49 (0) 77 20 95 71 73

### Finnland/ Finland

#### SKS-teknikka Oy

Martinkyläntie 50  
01720 Vantaa  
Finnland/ Finland  
Tel. +358 (09) 852 661  
Fax +358 (09) 852 68 20  
SKS-teknikka@SKS.Fi

### Frankreich/ France

#### Binder Magnetic

1, Allée des Barbanniers  
92632 Gennevilliers Cedex  
Frankreich/ France  
Tél. +33 (01) 46 13 80 80  
Fax +33 (01) 46 13 80 99  
info@binder-magnetic.fr  
www.bindermagnete.com

### Italien/ Italy

#### Binder Magnete S.r.l.

Centro Direzionale  
E Commerciale T 4  
20068 S. Felicino  
Italien/ Italy  
Peschiera Borromeo (Mi)  
Tel. +39 (02) 753 20 12  
Fax +39 (02) 753 36 96  
bindermagnete@tin.it  
www.binder-magnete.it

### Niederlande/ Netherlands

#### Solar Elektro BV

Postfach 183  
Postbus 183  
6920 AD Duiven  
Niederlande/ Netherlands  
Tel. +31 (026) 365 2911  
Fax +31 (026) 365 2220  
algemeen@solarelektr.nl

### Norwegen/ Norway

#### Industrielementer AS

Postboks 43  
1556 Son  
Norwegen/ Norway  
Tel. +(47) 64 95 81 32  
Fax +(47) 64 98 29 29  
post@industrielementer.no  
www.industrielementer.no

### Österreich/ Austria

#### Kendrion Binder Magnete Vertriebs GmbH

Estermannstrasse 27  
Postfach 79  
4017 Linz  
Österreich/ Austria  
Tel. +43 (0) 732 77 63 83  
Fax +43 (0) 732 78 35 58  
office@kendrion-binder.at  
www.kendrion-binder.at

#### Kendrion Binder Magnete GmbH

Postfach 42  
8552 Eibiswald 269  
Österreich/ Austria  
Tel. +43 (0) 34 66 423 220  
Fax +43 (0) 34 66 427 22  
office@kendrion.com

### Schweden/ Sweden

#### Industrikomponenter AB

Industrivägen 12  
17148 Solna  
Schweden/ Sweden  
Tel. +46 (08) 514 844 00  
Fax +46 (08) 514 844 01  
info@inkom.se  
www.inkom.se

### Schweiz/ Switzerland

#### Kendrion Binder Magnet AG

Albisstrasse 26  
8915 Hausen a/A  
Schweiz/ Switzerland  
Tel. +41 17 64 80 60  
Fax +41 17 64 80 69  
binder.magnet@kendrion.com  
www.kendrion.ch

### Spanien, Portugal/ Spain, Portugal

Binder Magnete Iberica S.L.  
Apartado de Correos 116  
Costa Zefir, 99  
c/de Cuba 16  
43892 Miami-Playa (Tarragona)  
Spanien/ Spain  
Tel. +34 (977) 17 27 07  
Fax +34 (977) 17 01 82  
binder@binder-es.com  
www.binder-es.com

### Süd Afrika/ South Africa

Magnete Service Binder SA CC  
26 Saal Street  
Kya Sand  
P.O. Box 44051  
Randburg 2194  
Linden 2104  
Süd Afrika/ South Africa  
Tel. +27 (11) 462 320/09/28/29  
Fax +27 (11) 462 3304  
info@binder.co.za

### Sonstige Länder/ Other Countries

Kendrion Binder Magnete (U.K.)  
Ltd.  
Huddersfield Road, Low Moor  
Bradford, West Yorkshire,  
BD 12 0TQ  
Großbritannien/ Great Britain  
Tel. +44 (0) 12 74 60 11 11  
Fax +44 (0) 12 74 69 10 93  
peter@kendrion-binder.co.uk  
www.kendrion-binder.co.uk

Kendrion Binder Magnete GmbH  
Power Transmission  
Mönchweilerstrasse 1  
78048 Villingen-Schwenningen  
Deutschland/ Germany  
Phone: +49 7721 877 -417  
Fax: +49 7721 877 -462  
www.kendrion-electromagnetic.com  
sales-kpt@kendrion.com





Kendrion Binder Magnete GmbH  
Power Transmission  
Mönchweilerstrasse 1  
78048 Villingen-Schwenningen

Phone: +49 7721 877-417  
Fax: +49 7721 877-462

[www.kendrion-electromagnetic.com](http://www.kendrion-electromagnetic.com)  
[sales-kpt@kendrion.com](mailto:sales-kpt@kendrion.com)

VARIO LINE

POWER OF PARTNERSHIP AND MAGNETISM