



### Ordering data

6SL3224-0BE35-5UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
<b>Input</b>		<b>Power factor <math>\lambda</math></b>	0.85
<b>Number of phases</b>	3 AC	<b>Offset factor <math>\cos \phi</math></b>	0.95
<b>Line voltage</b>	380 ... 480 V $\pm 10$ %	<b>Efficiency <math>\eta</math></b>	0.97
<b>Line frequency</b>	47 ... 63 Hz	<b>Sound pressure level (1m)</b>	60 dB
<b>Rated current with line reactor</b>	151.00 A	<b>Power loss</b>	1.93 kW
<b>Rated current without line reactor</b>	168.00 A	<b>Ambient conditions</b>	
<b>Output</b>		<b>Cooling</b>	Internal air cooling
<b>Number of phases</b>	3 AC	<b>Cooling air requirement</b>	0.150 m <sup>3</sup> /s
<b>Rated voltage</b>	400 V	<b>Installation altitude</b>	1000 m
<b>Rated power (LO)</b>	75.00 kW	<b>Ambient temperature</b>	
<b>Rated power (HO)</b>	55.00 kW	<b>Operation LO</b>	0 ... 40 °C (32 ... 104 °F)
<b>Rated current (LO)</b>	145.00 A	<b>Operation HO</b>	0 ... 50 °C (32 ... 122 °F)
<b>Rated current (HO)</b>	110.00 A	<b>Transport</b>	-40 ... 70 °C (-40 ... 158 °F)
<b>Max. output current</b>	220.00 A	<b>Storage</b>	-25 ... 55 °C (-13 ... 131 °F)
<b>Pulse frequency</b>	4 kHz	<b>Relative humidity</b>	
<b>Output frequency for vector control</b>	0 ... 200 Hz	<b>Max. operation</b>	95 % RH, condensation not permitted
<b>Output frequency for V/f control</b>	0 ... 550 Hz		

### Overload capability

#### Low Overload (LO)

1.1 × output current rating (i.e., 110 % overload) for 57 s with a cycle time of 300 s 1.5 × output current rating (i.e., 150 % overload) for 3 s with a cycle time of 300 s

#### High Overload (HO)

1.5 × output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 × output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240




Ordering data

6SL3224-0BE35-5UA0

Mechanical data	Connections
Degree of protection	Line side
Size	Version
Net weight	Conductor cross-section
Width	Motor end
Height	Version
Depth	Conductor cross-section
Converter losses to EN 50598-2*	DC link (for braking resistor)

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-59.87 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

\*calculated values; increased by 10% according to the standard

Conductor cross-section	25.00 ... 120.00 mm²
-------------------------	----------------------

Max. motor cable length	
Shielded	50 m
Unshielded	100 m

Standards	
Compliance with standards	UL, cUL, CE, C-Tick, SEMI F47
CE marking	According to low-voltage directive 2006/95/EC